

IRF540

Rev.G Jul.-2018

描述 / Descriptions

TO-220 塑封封装 N 沟道 MOS 场效应管。N-CHANNEL MOSFET in a TO-220 Plastic Package.

特征 / Features

低电阻,开关速度快。


Low on-resistance, low crss, fast switching.

用途 / Applications


用于高效 DC/DC 转换和功率开关。

These devices are well suited for high efficiency switching DC/DC converters and switch mode power supplies.

内部等效电路 / Equivalent Circuit



引脚排列 / Pinning



PIN1 : G

PIN 2 : D

PIN 3 : S

放大及印章代码 / h_{FE} Classifications & Marking

见印章说明。 See Marking Instructions.

极限参数 / Absolute Maximum Ratings(Ta=25°C)

参数 Parameter	符号 Symbol	数值 Rating	单位 Unit
Drain-Source Voltage	V_{DSS}	100	V
Drain Current	$I_D(T_c=25^\circ\text{C})$	28	A
	$I_D(T_c=100^\circ\text{C})$	20	A
Pulsed Drain Current	I_{DM}	110	A
Gate-Source Voltage	V_{GSS}	± 20	V
Single Pulsed Avalanche Energy	E_{AS}	230	mJ
Repetitive Avalanche Energy	E_{AR}	15	mJ
Avalanche Current	I_{AR}	28	A
Total Power Dissipation	$P_D(T_c=25^\circ\text{C})$	150	W
Storage Temperature Range	T_J, T_{STG}	-55 to 175	$^\circ\text{C}$
Thermal resistance junction to Case	$R_{\theta JC}$	1.0	$^\circ\text{C/W}$
Case to Sink, Flat, Greased, Surface	$R_{\theta CS}$	0.50	
Thermal resistance junction to Ambient	$R_{\theta JA}$	62	





电性能参数 / Electrical Characteristics(Ta=25°C)

参数 Parameter	符号 Symbol	测试条件 Test Conditions	最小值 Min	典型值 Typ	最大值 Max	单位 Unit
Zero Gate Voltage Drain Current	V_{DSS}	$V_{GS}=0V$ $I_D=250\mu A$	100			V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=100V$ $V_{GS}=0V$			25	μA
		$V_{DS}=80V$ $T_J=125^\circ\text{C}$			250	μA
Gate-Body Leakage Current Forward	I_{GSS}	$V_{GS}=\pm 20V$			± 100	μA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS}=V_{GS}$ $I_D=250\mu A$	2.0		4.0	V
Forward Transconductance	g_{FS}	$V_{DS}=50V$ $I_D=17A$	8.7			S
Static Drain-Source On-Resistance	$R_{DS(on)}$	$V_{GS}=10V$ $I_D=17A$			0.077	Ω
Forward On Voltage	V_{SD}	$V_{GS}=0V$ $I_S=18A$			2.5	V
Input Capacitance	C_{iss}	$V_{DS}=25V$ $V_{GS}=0V$ $f=1.0\text{MHz}$		1700		pF
Output Capacitance	C_{oss}			560		
Reverse Transfer Capacitance	C_{rss}			120		





电性能参数 / Electrical Characteristics(Ta=25°C)

参数 Parameter	符号 Symbol	测试条件 Test Conditions	最小值 Min	典型值 Typ	最大值 Max	单位 Unit
Turn-On Delay Time	$t_{d(on)}$	$V_{DD}=50V$ $I_D=17A$ $R_G=9.1\Omega$ $R_D=2.9\Omega$		11		ns
Turn-On Rise Time	t_r			44		
Turn-Off Delay Time	$t_{d(off)}$			53		
Turn-Off Fall Time	t_f			43		
Total Gate Charge	Q_g	$I_D=17A$ $V_{DS}=80V$ $V_{GS}=10V$		72		nC
Gate Source Charge	Q_{gs}			11		
Gate Drain Charge	Q_{gd}			32		
Reverse Recovery Time	t_{rr}	$T_J=25^\circ C$ $I_F=17A$		180	360	ns
Reverse Recovery Charge	Q_{rr}			1.3	2.8	μC

电参数曲线图 / Electrical Characteristic Curve




电参数曲线图 / Electrical Characteristic Curve




外形尺寸图 / Package Dimensions

TO-220

单位: mm



印章说明 / Marking Instructions



说明：

BR： 为公司代码

IRF540： 为产品型号

****： 为生产批号代码，随生产批号变化。


Note:

BR: Company Code

IRF540: Product Type.

****: Lot No. Code, code change with Lot No.

波峰焊温度曲线图(无铅) / Temperature Profile for Dip Soldering(Pb-Free)



说明：

- 1、预热温度 25 ~ 150°C，时间 60 ~ 90sec;
- 2、峰值温度 255±5°C，时间持续为 5±0.5sec;
- 3、焊接制程冷却速度为 2 ~ 10°C/sec.

Note:

- 1.Preheating:25~150°C, Time:60~90sec.
- 2.Peak Temp.:255±5°C, Duration:5±0.5sec.
3. Cooling Speed: 2~10°C/sec.

耐焊接热试验条件 / Resistance to Soldering Heat Test Conditions

温度：270±5°C

时间：10±1 sec.

Temp.:270±5°C

Time:10±1 sec

包装规格 / Packaging SPEC.

散件包装 / BULK

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Bag 只/袋	Bags/Inner Box 袋/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Bag 袋	Inner Box 盒	Outer Box 箱
TO-220/F	200	10	2,000	5	10,000	135×190	237×172×102	560×245×195

套管包装 / TUBE

Package Type 封装形式	Units 包装数量					Dimension 包装尺寸 (unit: mm ³)		
	Units/Tube 只/套管	Tubes/Inner Box 套管/盒	Units/Inner Box 只/盒	Inner Boxes/Outer Box 盒/箱	Units/Outer Box 只/箱	Tube 套管	Inner Box 盒	Outer Box 箱
TO-220/F	50	20	1,000	5	5,000	532×31.4×5.5	555×164×50	575×290×180

使用说明 / Notices