


JSD100

Description:

- 1) Low forward voltage and leakage current
- 2) Low inductance package
- 3) High surge current capability



D1


Typical Application:

- 1) Field supply for DC motors
- 2) Line rectifiers for transistorized AC motor controllers
- 3) Non-controllable rectifiers for AC/DC converter

Absolute Maximum Ratings (Packaged into D1, unless otherwise specified, $T_{CASE}=25^{\circ}\text{C}$)

Parameter	Test Conditions	Symbol	Values				Unit
			16	18	20	22	
Junction temperature range		T_J	-40~+150				°C
Storage temperature range		T_{STG}	-40~+125				°C
Repetitive peak reverse voltage		V_{RRM}	1600	1800	2000	2200	V
Non-repetitive peak reverse voltage		V_{RSM}	1700	1900	2100	2300	V
Output current	$T_C=95^{\circ}\text{C}$	I_D	100				A
Forward surge current	1/2 cycle, Sine wave	I_{FSM}	1000				A
Value for fusing	50Hz, $T_J=25^{\circ}\text{C}$	I^2t	5000				A^2s
RMS isolation voltage	A.C 50Hz(1s/1min)	V_{isol}	3600/3000				V



Three Phase Rectifier Bridge Module

Electrical Characteristics (Packaged into D1, unless otherwise specified, $T_{CASE}=25^{\circ}\text{C}$)

Parameter	Test Conditions	Symbol	Values			Unit
			Min.	Typ.	Max.	
Forward voltage	$I_F=100\text{A}, T_J=25^{\circ}\text{C}$	V_{FM}	-	-	1.35	V
Reverse leakage current	$V_R=V_{RRM}, T_J=25^{\circ}\text{C}$	I_{RRM}	-	-	0.5	mA
	$V_R=V_{RRM}, T_J=150^{\circ}\text{C}$		-	-	10	mA
Threshold voltage	$T_J=150^{\circ}\text{C}$, for power loss calculation only	V_{TO}	-	-	0.85	V
Slope resistance		r_T	-	-	4.0	mΩ


Thermal Characteristics (Packaged into D1, unless otherwise specified, $T_{CASE}=25^{\circ}\text{C}$)

Parameter	Test Conditions	Symbol	Values			Unit
			Min.	Typ.	Max.	
Thermal impedance (junction to case)	Per diode	$R_{th(j-c)}$	-	-	0.9	°C/W
Mounting torque	Module and heatsink fixed torque, screw M5	M	4.25	-	5.75	Nm
	Electrode connection torque, screw M5		4.25	-	5.75	Nm
Weight			132			g
Case style			D1			

Ordering Information

<u>JS</u>	<u>D</u>	<u>100</u>	<u>/16</u>
JieJie Semiconductor Co.,Ltd			
	Diode module	$I_D=100\text{A}$	16: $V_{RSM} \geq 1700\text{V}$ 18: $V_{RSM} \geq 1900\text{V}$ 20: $V_{RSM} \geq 2100\text{V}$ 22: $V_{RSM} \geq 2300\text{V}$

Mechanical Characteristics(mm)



Performance Curves

FIG.1: Forward characteristics(per diode)




FIG.3: Forward current vs. case temperature




FIG.2: Peak on-state surge current





FIG.4: Maximum transient thermal impedance





Three Phase Rectifier Bridge Module

Information furnished in this document is believed to be accurate and reliable. However, JieJie Semiconductor Co.,Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it.

Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information.

This document is the 1.3rd version which is made in 9-July-2022. This document supersedes and replaces all information previously supplied.

 is registered trademarks of JieJie Semiconductor Co.,Ltd. Copyright©2022 Semiconductor Co.,Ltd. Printed All rights reserved.