



- Thread spec.: Metric
- Material: Parts A, C, E are made of UL approved nylon PA66, parts B and D are made of Nitrile butadiene rubber (NBR).
- Working temperature: -40°C to 100°C in static state, instantaneous heat resistance up to 120°C ; -20°C to 80°C in dynamic state, instantaneous heat resistance up to 100°C .
- Characteristics: Special design of clamping die and rubber part, large range in clamping cable, ultra-strong stretching resistance, waterproof, dustproof, and high ability to resist salt, acid, alkali, alcohol, grease and general solvent.
- Color: Black(RAL9005), light grey (RAL7035), silver(RAL7001) as well as special colors that can be designed at request.

Technical Parameters

Model	Thread Size	Cable Range (mm)	Thread O.D. L2(mm)	Thread Length L1(mm)	Spanner Size A & E(mm)
MG12	M12×1.5	4.5~8	12	9	18/19
MG12	M12×1.5	3~5.3	12	9	18/19
MG16	M16×1.5	6~10	16	15	22/22
MG16	M16×1.5	4~7	16	15	22/22
MG20	M20×1.5	9~14	20	15	27/27
MG20	M20×1.5	6~11	20	15	27/27
MG25	M25×1.5	13~18	25	15	33/33
MG25	M25×1.5	10~16	25	15	33/33
MG32	M32×1.5	18~25	32	15	41/41
MG32	M32×1.5	15~22	32	15	41/41
MG40	M40×1.5	24~30	40	20	50/50
MG40	M40×1.5	20~25	40	20	50/50
MG50	M50×1.5	31~41	50	22	60/62
MG50	M50×1.5	26~32	50	22	60/62
MG63	M63×1.5	44~51	63	25	75/75
MG63	M63×1.5	40~46	63	25	75/75
MG90	M90×2.0	66~77	90	25	110/110
MG90	M90×2.0	58~68	90	25	110/110

Structural Drawing

